

Model ASC 300-L (950 MHz to 2050 MHz) Beacon Tracking Receiver

Quality Products @ Reasonable Prices



Functional Description

The Model **ASC300-L Beacon Tracking Receiver** is a high performance unit that is designed to real time track the power density of a satellite beacon and output a DC voltage that is linearly proportional to the beacon power by utilizing a true, RMS-responding power detector. The applications for the **ASC300-L** are for antenna step track controlling and uplink power control system.

Systems Specifications

Input Frequency.....950 MHz to 2050 MHz
 Pre-detection Bandwidth.....40 kHz
 Input Level.....-80 dBm, min.; -50 dBm max.
 For full tracking range capability
 Frequency Tuning.....10 kHz Steps
 Frequency Adjust.....Front Panel or Remotely
 AFC.....+20kHz
 Threshold.....<45 dB-Hz (C/N₀) for acquisition
 Input Impedance.....75 Ohm
 Input Connector.....Type-F, Female
 Output Impedance.....100 Ohm, single ended
 Output Connector.....Terminal plug and
 BNC Female
 Tracking Gradient.....0.5 V/dB, Std
 Tracking Response.....0 to +10 VDC
 for a 20 dB input level change
 System Level Adjust.....30 dB, Linear
 Frequency Stability.....<1 ppm, 0^oc to +50^o c
 Frequency Reference.....10 MHz (Internal)
 Phase Noise.....>75 dB-Hz, 1 kHz from Carrier

Alarms.....Unit Lock
 Alarm Relay.....Form-C
 External LNB Power.....+24 VDC, switchable In-Out,
 .500 ma, max. +15 and +18 VDC Optional
 Continuous Digital Streaming (CDS)....DB-9, RS-232
 (optional) See Below *
 Front Panel Display.....Vacuum Fluorescent
 M&C.....RS-232 or RS-422/485 Switchable on rear
 panel Ethernet 10/100 Base T (**Optional**)
 M&C Connector.....DB-9, Female
 RJ-45 Jack connector

Physical Characteristics

Size.....1.75"H X 16.00"D X 19.00"W
 Weight.....8 lb. (3.63 kg)
 Primary Power.....90 - 264 VAC 47 - 63Hz, 1.4 A
 AutoSensing

Environmental Specifications:

Operating Temperature.....0^oc to +50^o c
 Storage Temperature.....-40^oc to +70^o c
 Humidity.....95% RH@ 40^o c

ATLANTIC SATELLITE CORPORATION

**200 Expressway Court
Virginia Beach, Virginia 23462**

Phone: 757-318-3500
 Fax: 757-318-7020
 Email: sales@atlanticsat.com
 www.atlanticsat.com

* CDS Continuous Digital Streaming

The streaming option associated with the ASC300 series of beacon tracking receivers provides a continuous, two byte, data stream running at 2400 baud that contains twelve bits of signal strength level indication as well as lock or alarm condition of the unit. Other baud rates are available. A female DB9, RS-232, interface connector on the rear of the unit is specifically dedicated for this option.